



| Characteristics                                    | Mirage Classic   |  |
|--|--|--|
| Description  | <ul style="list-style-type: none"> <li>• Solid prefinished hardwood flooring with tongues and grooves</li> <li>• Micro-V bevel (on 4 sides)</li> </ul>   |  |
| Thickness  | 3/4" (19 mm)   |  |
| Width  | 3-1/4" (83 mm)   | 4-1/4" (108 mm)  |
| Length <sup>1</sup>                                | Random lengths from 10" (250 mm) to 76" (1,930 mm)   |  |
| Installation                                       | Nailed or stapled down (above and on grade)  |  |
| Subfloor   | Wood   |  |
| Species  | 4 species: Red Oak, Oak, White Oak, Maple  |  |
| Grade  | <ul style="list-style-type: none"> <li>• <b>Exclusive:</b> Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a limited range of color variation.</li> <li>• <b>Elemental:</b> The Elemental grade offers a wider concentration of color variation than the Exclusive grade. They feature wood planks with some pronounced and nuanced coloration, small open and closed knots, and mineral streaks.</li> <li>• <b>Character:</b> These floors are appreciated for their pronounced color variations. They feature open and closed knots, mineral streaks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment.</li> </ul> |  |
| Color choice<br>(refer to 2025 Mirage Collections) | Some products may not be available. Ask your Mirage representative or consult the <a href="#">Product Chart</a> .  |  |
| Finish   | Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. <ul style="list-style-type: none"> <li>• DuraMatt® (5% gloss)</li> <li>• DuraMatt® X (10% gloss)</li> <li>• DurAlive™ (12% gloss)</li> <li>• Cashmere* uses Nanolinx® technology (18% gloss)</li> <li>• Nanolinx® Commercial (18% gloss)</li> </ul> UV Protection: All products<br>Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5   |  |
| Applicable standards                               | <b>Surface Burning (ASTM-E-84):</b> <ul style="list-style-type: none"> <li>• FSI (Flame Spread Index) 100 to 150 Class C (depends on wood species)</li> <li>• SD (Smoke Development) 75 to 400 (depends on wood species)</li> </ul> <b>Critical radiant flux (ASTM-E-648-94a):</b><br>0.25 to 0.40 watt/cm <sup>2</sup> (depends on wood species)  | <b>Surface Burning (ULC-S-102-2):</b> <ul style="list-style-type: none"> <li>• FSV (Flame Spread Value) 100 to 150 (depends on wood species)</li> <li>• SD (Smoke Development) 200 to 300 (depends on wood species)</li> </ul> <b>R value:</b><br>R 0.6 to 0.8 (depends on wood species) |
|  | <b>Formaldehyde and VOC emissions (CDPH 1.2, 2017) :</b> Target product group (Classic) conform  |  |
| Provenance   | Made in St-Georges, Qc, Canada.  |  |
| Use  | Residential, light commercial or commercial  |  |
| Accessory  | Round Stair Nosing, Square Stair Nosing, Matchable Square Stair Nosing, Round Reducer, Threshold, "T" Molding, Quarter Round, Wood Flush Mount Vent, Treads & Risers   |  |
| Warranty   | <ul style="list-style-type: none"> <li>• Structural <b>lifetime</b> limited warranty (Relative humidity must always be maintained within a range of 35% and 55%).</li> </ul>   | <ul style="list-style-type: none"> <li>• <b>35-year</b> finish warranty for residential applications</li> <li>• <b>3-year</b> finish warranty for light commercial applications</li> <li>• <b>5-year</b> finish warranty for commercial with Nanolinx® Commercial</li> </ul>             |
| Packaging  | 3-1/4" (83 mm)   | 4-1/4" (108 mm)  |
| Content of a box                                   | • 20 sq. ft.   | • 18 sq. ft.   |
| Size of a box                                      | • 79-1/2" L x 10-1/4" W x 3-1/4" H   | • 86" L x 9" W x 3-1/4" H  |
| Weight of a box                                    | • 51 to 59 lb  | • 46 to 53 lb  |
| Content of a pallet                                | • 48 boxes = 960 sq. ft. (4 boxes/W x 12 boxes/H)  | • 48 boxes = 864 sq. ft. (4 boxes/W x 12 boxes/H)  |
| Size of a pallet                                   | • 79-1/2" L x 42" W x 42" H  | • 86" L x 37" W x 42" H  |
| Relative species hardness                          |  |  |
| NWFA Janka Test                                    | • Red Oak  | 1,290 lbs - average hardness   |
| Hardness test (ASTM-D-143)                         | • Oak  | 1,290 lbs - average hardness   |
|  | • White Oak  | 1,360 lbs - 5% harder  |
| Red Oak 1290 lbs* - 100%                           | • Maple  | 1,450 lbs - 12% harder   |
| *lbs = Applied force in pounds                     |  |  |

\* Cashmere is a registered trademark used under license.

1. Values in millimeters have been rounded to the nearest unit. Please refer to values in inches to get the exact planks value.